



SUPERIOR PRODUCTS INTERNATIONAL II, INC.

Application Equipment (5/05)

The following is a guide. Changes in pressures and tip sizes may be needed for proper spray characteristics. Always purge spray equipment before use with reducer (acetone or MEK). Any reduction must be compatible with the existing environmental and application conditions. Refer to product application instructions for detailed application information.

<u>Product Name:</u>	<u>Type of Equipment</u>	<u>Tip Size</u>
<u>Group 1:</u>		
ENAMO GRIP	Air Pot or Airless	.015" - .019"
GRAFITTI CLEANER	Air Pot or Airless	.015" - .019"
INNER SEAL	Air Pot or Airless	.015" - .019"
ULTRACIDE	Air Pot or Airless (Air Pot at 45 psi)	.015" - .019"
<u>Group 2:</u>		
ENAMO GRIP W/B	Air Pot or Airless	.017" - .021"
LINING KOTE	Air Pot or Airless	.017" - .021"
MOIST METAL GRIP	Air Pot or Airless	.017" - .021"
RUST GRIP	Air Pot or Airless	.017" - .021"
TOTAL SEAL	Air Pot or Airless (Air Pot at 45 psi)	.017" - .021"
<u>Group 3:</u>		
EPOXOTHERM*	Air Pot or Airless	.029" - .033"
SUNSHIELD 2000*	Air Pot or Airless	.029" - .033"
SUPERBASE(HS)*	Air Pot or Airless	.029" - .033"
SUPER THERM*	Air Pot or Airless	.029" - .033"
TOTAL SEAL (HS)	Air Pot or Airless (Air Pot at 60 psi)	.029" - .033"
<u>Group 4:</u>		
SP2001F*	Texture Sprayer	3-4 mm nozzle
HOT PIPE COATING*	Texture Sprayer	3-4 mm nozzle
ACRYLIC STUCCO	Texture Sprayer	flexhead/pole spray

Equipment:

Group 1 & 2:	Graco or Binks - 5-horse power (Model: 7500 pumps 1.5 gal/min at 3000 psi)
Group 3:	Graco or Binks - 10 horse power (Model 10000 pumps 2.5 gal/min at 3000 psi)
Group 4:	Graco Texspray 1500 or equivalent (RotoFlex or Carousel Style pumps at 2 gal/min at 100 psi) Use a Texture Flexhead and Pole Spray Gun for Acrylic Stucco Use Graco King 68:1 or equivalent for smoother finish for SP2001F

* Remove filters from spray equipment and spray guns before spraying coatings containing ceramics